



磨 丸

外 径	kg/m	定尺
3.0	0.056	1M
4.0	0.099	2M
5.0	0.154	2M
6.0	0.222	4M
7.0	0.302	4M
8.0	0.395	4M
9.0	0.499	4M
9.52	0.560	4M
10.0	0.617	4M
11.0	0.746	4M
12.0	0.888	4M
12.7	0.997	4M
13.0	1.04	4M
14.0	1.21	4M
15.0	1.39	4M
16.0	1.58	4M
17.0	1.78	4M
18.0	2.00	4M
19.0	2.23	4M
20.0	2.47	4M
21.0	2.72	4M
22.0	2.98	4M
23.0	3.26	4M
24.0	3.55	4M
25.0	3.85	4M・6M
26.0	4.17	6M
27.0	4.49	6M
28.0	4.83	6M
29.0	5.18	6M
30.0	5.55	6M
31.0	5.93	6M
32.0	6.31	6M
33.0	6.71	6M
34.0	7.13	6M
35.0	7.55	6M
36.0	7.99	6M
38.0	8.90	6M
40.0	9.87	6M
42.0	10.9	6M
45.0	12.5	6M
46.0	13.0	6M
48.0	14.2	6M
50.0	15.4	6M
55.0	18.7	6M
60.0	22.2	6M
65.0	26.0	6M
70.0	30.2	6M
75.0	34.7	6M
80.0	39.5	6M
85.0	44.5	6M
90.0	49.9	6M
100.0	61.7	6M
110.0	74.6	6M
120.0	88.8	6M

磨 角

外 径	kg/m	定尺
4.0	0.126	2M
5.0	0.196	2M
6.0	0.283	4M
7.0	0.385	4M
8.0	0.502	4M
9.0	0.636	4M
9.52	0.711	4M
10.0	0.785	4M
11.0	0.95	4M
12.0	1.13	4M
12.7	1.27	4M
13.0	1.33	4M
14.0	1.54	4M
15.0	1.77	4M
16.0	2.01	4M
17.0	2.27	4M
18.0	2.54	4M
19.0	2.83	4M
20.0	3.14	4M
22.0	3.80	4M
24.0	4.52	4M
25.0	4.91	4M
26.0		4M
28.0	6.15	4M
30.0	7.07	4M
32.0	8.04	4M
35.0	9.62	4M
36.0	10.2	4M
38.0	11.3	4M
40.0	12.6	4M
42.0	13.8	4M
44.0	15.2	4M
45.0	15.9	4M
50.0	19.6	4M
55.0	23.7	4M
60.0	28.3	4M
70.0	38.5	4M
75.0	44.2	4M
80.0	50.2	4M
85.0	56.7	4M
90.0	63.6	4M
95.0	70.9	4M

六 角 鋼

外 径	kg/m
6.0	0.245
7.0	0.333
8.0	0.435
9.0	0.55
10.0	0.68
12.0	0.981
13.0	1.15
22.0	3.29
29.0	5.71
38.0	9.81
42.0	
50.0	17.0
58.0	22.8
63.0	27.0
66.0	
70.0	33.3
75.0	38.3
80.0	43.5

☆ 原則的に磨き材は乱尺です
☆ S45C等取り扱いあります。